

According to the Construction Products (Amendment etc.) (EU Exit) Regulations 2019/2020

1. Unique identification code of the product-type :

**Plate S460N / 1.8901**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

**Plates S460N / 1.8901 according to EN 10025-3**

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer :

**Welded, bolted and riveted structures**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5) :

**INDUSTEEL France  
Site de Châteauneuf  
118 Route des Etaings  
42800 Châteauneuf  
France  
Tél : +33 477752007**

**e-mail : [info.dopil@arcelormittal.com](mailto:info.dopil@arcelormittal.com)**

**Link : <https://industeel.arcelormittal.com/downloads/certifications-quality/>**

5. Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2) :

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V :

**System 2+**

7. In case of the declaration of performance concerning a construction product covered by a designated standard :

**Approved factory production control certification body, body TUV SUD BAPTUNLIMITED, Nr 0168 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control nr 0168 - CPR – M - 008 – 2023 rev1.**

According to the Construction Products (Amendment etc.) (EU Exit) Regulations 2019/2020

## 8. Declared performance

Essential characteristic		Performances			Designated technical specification
Tolerance on dimensions /shape	Thickness		EN 10029 Class A		
	Flatness		EN 10029 Class N		
Yield strength	Nominal thickness (mm)		Imposition		
	>	≤	Min (MPa)		
	100	150	380		
	150	200	370		
Tensile strength	Nominal thickness (mm)		Imposition		
	>	≤	min (MPa)	max (MPa)	
	100	150	530	710	
	150	200	530	710	
Elongation	Nominal thickness (mm)		Imposition		
	>	≤	min (%)		
	100	150	17		
	150	200	17		
Impact strength	Nominal thickness (mm)		Imposition		
	>	≤	T (°C)	Min Kv (J) transversale direction	Min Kv (J) longitudinale direction
	100	200	-20	20	40
			-10	24	43
			0	27	47
20			31	55	
Chemical composition	Nominal thickness (mm)		Imposition		
	>	≤	Elément	min (%)	max (%)
	100	200	C		0.20
			Si		0.60
			Mn	1.00	1.70
			P		0.030
			S		0.025
			Nb		0.05
			V		0.20
			Al <sub>total</sub> *	0.02	
			Ti		0.05
			Cr		0.30
			Ni		0.80
			Mo		0.10
Cu				0.55	
N		0.025			
Weldability	Nominal thickness (mm)		Imposition		
	>	≤	CEV (%max)		
	100	200	0.55		

**EN 10025-3 : 2019**

\* When other nitrogen binding elements are used, the minimum Al value does not apply.

9. The performance of the product identified in points 1 & 2 is in conformity with the declared performance point 8.

This declaration Of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

**Aurélien CHAIZE**  
Metallurgical Eng.  
Châteauneuf, 2023-03-06

