

According to the Construction Products (Amendment etc.) (EU Exit) Regulations 2019/2020

1. Unique identification code of the product-type :

**Plate S355J0 / 1.0553**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :

**Plates S355J0 / 1.0553 according to EN 10025-2**

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer :

**Welded, bolted and riveted structures**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5) :

**INDUSTEEL France  
Site de Châteauneuf  
118 Route des Etaings  
42800 Châteauneuf  
France  
Tél : +33 477752007**

**e-mail : [info.dopil@arcelormittal.com](mailto:info.dopil@arcelormittal.com)**

**Link : <https://industeel.arcelormittal.com/downloads/certifications-quality/>**

5. Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2) :

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V :

**System 2+**

7. In case of the declaration of performance concerning a construction product covered by a designated standard :

**Approved factory production control certification body, TUV SUD BABTUNLIMITED, Nr 0168 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control nr 0168 - CPR – M - 008 – 2023 rev1.**

According to the Construction Products (Amendment etc.) (EU Exit) Regulations 2019/2020

## 8. Declared performance

Essential characteristic		Performances		Designated technical specification
Tolerances on dimensions / shape	Thickness		EN 10029 Class A	
	Flatness		EN 10029 Class N	
Yield strength	Nominal thickness (mm)		Values	
	>	≤	min (MPa)	
	100	150	295	
	150	200	285	
	200	250	275	
Tensile strength	Nominal thickness (mm)		Values	
	>	≤	min (MPa)	max (MPa)
	100	150	450	600
	150	200	450	600
	200	250	450	600
Elongation	Nominal thickness (mm)		Values	
	>	≤	min (%)	
	100	150	18	
	150	200	17	
	200	250	17	
Impact strength (longitudinal direction)	Nominal thickness (mm)		Values	
	>	≤	T (°C)	Min Kv (J)
	100	250	0	27
Chemical composition	Nominal thickness (mm)		Values	
	>	≤	Element	max (%)
	100	250	C	0.22
			Si	0.55
			Mn	1.60
			P	0.030
			S	0.030
			N	0.012
Cu	0.55			
Weldability	Nominal thickness (mm)		Values	
	>	≤	CEV (%max)	
	100	150	0.47	
	150	250	0.49	

EN 10025-2 : 2019

9. The performance of the product identified in points 1 & 2 is in conformity with the declared performance point 8.  
This declaration Of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Aurélien CHAIZE**  
Metallurgical Eng.  
Châteauneuf, 2023-03-06

